

## Steps to Making the Quilt

Step(s)	Date Completed
1. Properly press fabric, if needed	
2. Properly straighten the cross-wise grain on each fabric.	
3. Properly "cut" out two 6 in. x 45 in. strips out of color A, B & C. Show Ms. Black how to do the step <b>BEFORE</b> you actually cut out the first strip!	
4. Properly "cut" out each 6x45 in. strips into 6 in. squares. Show Ms. Black how to do the step <b>BEFORE</b> you actually cut out the first square! 12 squares from each color.	
5. Pin 6 A squares to 6 B squares RS tog	
6. Pin 6 B squares to 6 C squares RS tog	
7. Pin 6 C squares to 6 A squares RS tog	
8. Using a ½ inch seam, properly sew A squares to B squares together & press seams open.	
9. Using a ½ inch seam, properly sew B squares to C squares together & press seams open.	
10. Using a ½ inch seam, properly sew C squares to A squares together & press seams open.	
11. Following quilt square pattern, pin pairs (RS tog) to create column 1 using ½ in. seam	
12. Following quilt square pattern, pin pairs (RS tog) to create column 2 using ½ in. seam	
13. Following quilt square pattern, pin pairs (RS tog) to create column 3 using ½ in. seam	
14. Following quilt square pattern, pin column 1 to column 2 (RS tog) using ½ in. seam & press seam open	
15. Following quilt square pattern, pin column 1 & 2 to column 3 (RS tog) using ½ in. seam & press seam open	
16. Properly press quilt top	
17. Cut out batting/felt for quilt & pin quilt top to batting/felt	
18. Press back/border fabric and properly pin to quilt top w. batting/felt	
19. Create borders and make mitered corners for borders; properly pin (steps 20-22 on back)	

20. Using a blind stitch, hand sew quilt borders	
21. Properly hand sew the quilt lines	
22. Evaluate quilt using an assessment tool	